

Section 5

CELLULAR MOBILE PHONE ANTENNAS

Updated 18 February 2011

Vehicle Mounting Brackets and Springs



This selection of brackets are available to mount cellular mobile phone antennas in various positions on a vehicle. Each bracket has a 17 mm diameter hole through which the antenna is secured.



GM1

“L” bracket for Vehicle Guard

1.6 mm stainless steel
2 drilled holes for screws



GM2

“Z” bracket for Vehicle Guard

1.6 mm stainless steel
2 drilled holes for screws
1 drilled hole for bolt



BBM-SS

Bracket for Vehicle Bull Bar

50 mm diameter tube max
All stainless steel
Includes U-bolts, nuts and washers



MRM-SS

Bracket for Vehicle Mirror

20 mm diameter tube max
All stainless steel
Includes bolts, nuts and washers



TLM

Bracket for Vehicle Boot or Bonnet

All stainless steel
Rubber feet to protect painted surface
Includes Allen Key to tighten in position



GM

Bracket for Vehicle Guttering

All stainless steel
Includes screws and plate clamp

A spring dampens vehicle vibrations while travelling and reduces stress upon antenna components. These springs are available to order separately.



The **1570** spring will suit GIDM90T

The **1570** stainless steel spring is available as another mounting option for the GIDM90T cellular mobile phone antenna.

The drilled bolt and washer included allows feeder cable to pass through the centre of the spring and exit through the bolt.


- 50 mm tall x 20 mm diameter.
- M10 thread both ends



The **1269** spring as supplied with SGDB

A heavy duty and high quality stainless steel beehive spring, the **1269** has been successfully used on our popular SGDB antennas for decades.

- Includes a 1/2" bolt and spring washer.
- 105 mm tall x 45 mm diameter.
- 1/2"-12 BSW thread both ends.



The **1270** spring as supplied with TC1600

Our strongest most rigid heavy duty steel barrel spring, the **1270** is ideal for vehicle mounting very tall antennas such as the 2.2 metre Max-Gain TC1600 models.

Highly recommended when usual driving conditions are very rough.

- Includes a 1/2" bolt and spring washer.
- 105 mm tall x 35 mm diameter.
- 1/2"-12 BSW thread both ends.