

Section 9

ANTENNA MOUNTING ACCESSORIES

Updated 22 February 2011

Mobile Antenna Springs



A mobile antenna spring dampens vehicle vibrations while travelling and reduces stress upon antenna components. These springs are available to order separately.

MS Base



The "MS Base" medium duty stainless steel spring with 5/16"-26 TPI male and female threads will suit any mobile whip being mounted on to our OB-2 antenna bases. Screw the spring onto the base and the whip onto the spring.

- ⊖ 60 mm tall x 20 mm diameter.
- ⊖ 5/16"-26 TPI male and female threads.

1570



The drilled bolt and washer supplied with the "1570" stainless steel spring allows the antenna cable to pass through the centre of the spring and exit through the bolt. The spring will suit any antenna with M10 thread, such as our GRHFC or GIDM90T models.

- ⊖ 50 mm tall x 20 mm diameter.
- ⊖ M10 thread both ends.
- ⊖ Includes drilled bolt and spring washer.

1269



A high quality electro-polished stainless steel barrel spring, the "1269" has been used successfully on our popular SG series of antennas for decades.

- ⊖ 105 mm tall x 45 mm diameter.
- ⊖ 1/2"-12 BSW thread both ends.
- ⊖ Includes a 1/2"-12 BSW bolt and spring washer.

ZN4-SB



"ZN4-SB" consists of a high quality electro-polished stainless steel barrel spring together with a drilled bolt which allows the antenna cable to pass through the centre of the spring and bottom exit through the bolt. As used on ZN4-77-06 mobile UHF CB antenna and ZN4-77-02 ground independent base.

- ⊖ 105 mm tall x 45 mm diameter.
- ⊖ 1/2"-12 BSW thread in bottom, M10 thread in top.
- ⊖ Includes a drilled 1/2"-12 BSW bolt and spring washer.

1270



A strong and rigid heavy duty stainless steel parallel spring, the "1270" is ideal for mounting very tall antennas to a vehicle bull bar. This spring is supplied with our 2.2 metre Max-Gain TC series of mobile antennas. Highly recommended when usual driving conditions are very rough.

- ⊖ 105 mm tall x 45 mm diameter.
- ⊖ 1/2"-12 BSW thread both ends.
- ⊖ Includes a 1/2"-12 BSW bolt and spring washer

ZN3-SB-L



Large stainless steel barrel spring base and cable assembly.

Suit ZN3-77-12 super heavy and ZN3-77-11 heavy duty UHF CB mobile antennas.

- ⊖ 160 mm tall x 55 mm diameter.
- ⊖ Top mount UHF female connector.
- ⊖ 4.5 metres RG58 low loss cable.
- ⊖ 1/2"-12 BSW thread.
- ⊖ Includes drilled 1/2"-12 BSW bolt and spring washer.
- ⊖ Installation Kit containing Allen Hex Key, cable ties, PVC cap, UHF male connector, coil of solder.

ZN3-SB-S



Stainless steel barrel spring base and cable assembly.

Suit ZN3-77-10 medium duty UHF CB mobile antenna.

- ⊖ 150 mm tall x 45 mm diameter.
- ⊖ Top mount UHF female connector.
- ⊖ 4.5 metres RG58 low loss cable.
- ⊖ 1/2"-12 BSW thread.
- ⊖ Includes drilled 1/2"-12 BSW bolt and spring washer.
- ⊖ Installation Kit containing Allen Hex Key, cable ties, PVC cap, UHF male connector, coil of solder.